


Empty enclosure

AKi 3-gh



AKi 3-gh

Empty enclosure

CUSTOMIZABLE

Productnumber: 74390301

Dimensions: 300 x 450 x 209 mm

Empty Enclosure - Industrial Quality -, With double membrane seals, Sealing and insulating plugs, Base: glass fibre reinforced polycarbonate, light grey similar to RAL 7035, Cover: polycarbonate, light grey similar RAL 7035



Technical Data

electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Rated insulation voltage DC:	1000 V
Type of protection:	IP65
Protection class:	II

Colours

Cover colour:	grey
---------------	------

Dimensions

Length:	450 mm
Width:	300 mm

Dimensions

Height:	209 mm
---------	--------

Material characteristics

suitable for exterior use:	yes
Halogen free:	yes
Industry quality:	yes

mechanical properties

Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Cover screw torque:	1.2 Nm
Stackable:	yes
Impact strength:	IK08

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35
Max. ambient temperature:	80
24h ambient temperature:	60

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate, glass-fibre reinforced
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

ASS-gro - External hinge set

AK NS35-250 - Standard rail

AK ABL-ES - External fixing lugs

AK MPI 3 - Mounting plate

NS35-216/3 - Standard rail

NS 35-406 - Standard rail

AKi ABF 2 - Enclosure wall

AK TW - Partition wall